

## Culti-Packer Specifications

### STANDARD EQUIPMENT

- Pintle type hitch
- Heavy duty hitch Jack
- The main frame is fabricated from 4 x 8 heavy wall structural tubing
- Heavy duty, self-aligning triple sealed greasable radial steel ball bearings
- 17" diameter crow-foot packer wheels
- Extra large diameter rocker shafts with GSM nylon inserts that require no greasing
- Hardened steel bushings in hydraulic cylinder pin holes
- 2" cold rolled steel shafts with locking nuts at each end for easy access to bearings
- Extra large 2 1/4" replaceable wheel spindles
- Packer wheels roll on a large 8" pipe carried by 214 self aligning bearings on each end
- Two rolls of Hi-clearance Danish tines with 2 3/4" shovels on 6" spacing with hydraulic depth control
- Dual 16" 12 ply transport tires

### OPTIONAL EQUIPMENT

- V-Cog Packer wheels
- Clevis hitch
- 6OLM hubs on center frame
- Rear hitch for pull type seeder
- Mounted seeders
- Hydraulic accumulator on draw-bar for flotation control

P 1000 SERIES RIGID CULTI-PACKER						
MODEL	SIZE	HEIGHT FOLDED	TRANSPORT WIDTH	APPROX. WEIGHT	NO. OF CROW-FOOT PACKER WHEELS	NO. OF V-COG PACKER WHEELS (OPT)
P1016	16'		16'	6,400	55	79
P1018	18'		18'	7,200	63	91
P1020	20'		20'	8,000	71	102
P 3000 SERIES FOLDING CULTI-PACKER						
P3020	20'	9'-2"	14'-4"	12,600	71	105
P3024	24'	11'-4"	14'-4"	14,000	87	125
P3028	28'	12'-5"	14'-4"	15,300	97	140
P3030	30'	13'-0"	17'-4"	16,000	107	154
P3032	32'	13'-6"	17'-8"	16,500	115	161
P3035	35'	15'-2"	17'-8"	17,200	127	183
P3038	38'	16'-3"	17'-8"	18,000	135	195
P3040	40'	17'-4"	17'-8"	18,800	143	206

